



PRIMUS HOUSE WRAPS

Mfgd. by : GULNAR PLASTICS PVT LTD.





PRIMUS HOUSE WRAPS

Mfgd. by : GULNAR PLASTICS PVT LTD.



Primus

Primus is a crosswoven, micro-perforated, polypropylene house wrap. It is designed to protect exterior wall systems from bulk moisture infiltration.

Features

Primus can be converted into a drainable house-wrap. Primus is UV protected and can be exposed to elements for 6 months, without deterioration in quality. Primus comes with perforation, allowing moisture and vapor to escape. Primus thus also acts as an air barrier. Primus requires no maintenance

Size

Primus is usually available in width sizes, 3', 8', 9' and 10' and in roll lengths of 100', 150' and 195'.

Width per roll	3', 8', 9' & 10'
Length per roll	100', 150' & 195'
Rolls/Pallet (100')	112 Nos
Rolls/Pallet (150')	84 Nos
Rolls/Pallet (195')	77 Nos

Primus weighs about 25 lbs per 1000 sq ft.

Possibilities

Primus can be coated either on one side or on both the sides. Primus weighs about 65 gsm if coated on one side and 85 gsm if coated on both sides. As per your requirement, we can add a drainable feature to the house-wrap. Primus can be customized to suit all your requirements. We can customize

Printing Logos

Private Labels

Different Roll Lengths

Master Rolls

Any other requirement you might have.

Technical Data

APPLICABLE STANDARDS

ICC-ES EVALUATION REPORT ESR-3307

ASTM E 96 Standard Test Method for Water Vapor Transmission of Materials

ASTM D 882 Standard Test Method for Tensile Properties of Thin Plastic Sheeting

Installation

PRIMUS PLACEMENT

- Align bottom edge of roll to the bottom portion of the wall and unroll against the wall sheathing.
- Fasten with plastic cap nails, staples or large head nails. When installing over foam sheathing, fasteners should penetrate structural framing at least 1/2".
- Overlap all vertical seams a minimum of 6". Horizontal seams should be overlapped a minimum of 8".
- All seams, tears and protrusions should be taped with Primus House Wrap Tape or other appropriate tape.
- For window and door details refer to the Primus Installation Guide available from the manufacturer.

Protection and Warranty

The Primus Installation Guide contains detailed instructions on its installation. This is available on request.

Primus should be covered with the exterior cladding preferably within 180 days.

Primus comes with a 20 yr limited warranty.

Mfg by:

GULNAR PLASTICS PVT LTD.

Unit No.2, 1st Floor, Mahalaxmi Industrial Estate,

Gandhi Nagar, Lower Parel (W), Mumbai 400 013.

Tel +91 9833931220 | 0260 3919204 Fax 022-24970756

E info@gulnarplastics.com

